

# Art's Way

Since 1956

Introducing the  
**NEW**

## 6105 Grinder Mixer Hammermill



### Superior Feed Grinding Action

Additional 36 hammers – doubling the number of hammers to 72 – run faster grinding speeds and deliver a more consistent grind for excellent feed rations.

### Optional Features Offer Easier Operation

More base machine options offer combinations of hydraulic and manual operations for the Lift & Swing and Discharge Auger. Choose with or without Hydraulic Auger Feeder.

Portable Feed Grinding  
and Mixing System

[www.artsway-mfg.com](http://www.artsway-mfg.com)

*meeting your needs in the farmyard and feedlot*



# 6105 Grinder Mixer • Features • Specifications

Tank capacity	105 bu (130.7 cu ft)
PTO drive	540 RPM
HP requirement	40 - 100 HP
Feeder	gravity hopper or feed auger
Auger feeder length	96 in
Auger feeder auger diameter	10 in
Hammermill width	20 in
Grinder drive	6 double V-belts
Grinder hammers	72 hardened 4-way reversible
Grinder screen area	600 sq in
Screens	13 (1/8 in to 2 in)
Diameter of mixing auger	12 in dia. flighting, 13 in tube, 24 in base
Unloading auger tube diameter	8 in
Unloading auger standing reach at 60 degree	
Standard - no extension	16 ft 8 in
3 ft fold extension	19 ft 3 in
6 ft fold extension	22 ft
Unloading auger	316 degrees horizontal, infinite vertical
Tires	10 x 15 - 8 ply rib implement
Supplement hopper	21 in x 24 in
Overall height	8 ft 10 in (106 in)
Overall width without auger feeder	7 ft 11 in (95 in)
Overall length	14 ft 2 in (170 in)
Approx. weight without auger feeder	3,540 lbs
Ground clearance	10 in

## Standard features:

- 105 bushel tank
- One piece 20" Hammermill, 72 reversible hammers
- Four large inspection windows in tank
- Tongue jack
- Ladder and fenders
- 10:00 x 15 - 8 ply tires
- Throat magnet - #4 x 18" (24")
- Ingredient supplement hopper w/sack cutter
- Heavy duty implement drive line
- Weigh bars and spindles

## Optional features:

- Hydraulic auger feeder
- Swing arm scale support
- Scale systems
- Folding and bolt-on discharge auger extensions
- Grinder screens
- Hydraulic roll feed
- Hydraulic discharge auger



Optional scale system indicators for improving accuracy in feed formulation. Weigh bars and spindles are standard.



Base machine options include optional hydraulic lift and swing, discharge auger, and auger feeder.



Additional 4th inspection window on rear of the tank provides optimal viewing angle.



72 hardened 4 way reversible hammers for faster grinding speeds and more consistent grinds.



**Art's Way Manufacturing Co., Inc.**  
 PO Box 288 • Armstrong, IA 50514  
 (712) 864-3131 • Fax (712) 864-3154  
 sales@artsway-mfg.com  
 www.artsway-mfg.com

Art's Way Manufacturing Co., Inc. reserves the right to change design or specifications without notice. Information contained herein is general and is not intended for specific application purposes. Photographs contained herein may be displayed with safety shields and/or guards removed to show mechanical functions only. AW6105-114



MORE TOP PERFORMING ARTS WAY PRODUCTS